PRODUCT SPECIFICATIONS-LOOSE LAY FLOORING



Construction		
Color name	Wild Oak	
Color code	USA22258	
Size	1219. 2*177. 8mm	- nj.;
Thickness	5MM Loose lay	
Wear layer	20mil	
Pcs per Pack	12pcs	
Quantity per pack	28. 002SQ. FT	

Specification Sheet	Result	
Classification	42	
Density	1.95-2.00g/ cm³	
Peel Strength	2.8Kgf/2cm	
Chemical Resistance	Pass	
Colour Fastness to Artificia Light	Pass.≥Grade 6	
Castor Chair Suitabili	Pass Type W	P
Residual Indentation	Pass ≤0 1mm	

Artificia Light	Pass.≥Grade 6	
Castor Chair Suitabili	Pass Type W	1
Residual Indentation	Pass.≤0.1mm	
Abrasion Group	Group T	
Dimensional Stability	Pass 0.1%	
Curling	≤2mm	
Sound Reduction	2 db	
Slip Resistance	R10 Class DS	
Electrical Resistance	Pass	
Thermal Resistance	Pass 0.038m²K/V	
Fungus Resistance	NO Growth	
Behaviour to Fire	Bfl-S1	



Key Features









Scratch & Dent Resistant





ıg combines durability, style and waterproof technology to give you an unparalleled