





ULTRATHIN CANOPY SURFACE MOUNT 70W





- Features:
- Thin Appearance
 - Good Heat Dissipation
 - Convenient Installation
 - Pendant or Surface Mount
 - Long Life high Efficiency LEDs

DLC Part#: CN302D-70W-57K-10-BR

Product ID	Housing Color	Wattage	Lumens	CCT	Voltage	Dimming	Lumens/Watt
PWYY8C0I	Bronze	70W	8400	5700K	120-277	0-10V	120

PHOTOMETRY





ULTRATHIN CANOPY SURFACE MOUNT 70W

Technical Specifications:

Electrical:

Input Voltage: 120 thru 277

Current: .568A@120V; .284A@277V

Frequency: 60Hz

Power Factor: $\geq .9$

Product Parameters:

70 Watts

Efficacy: 120 lumens per watt

50,000+ LED Life Span

CCT: 5700k (Cool White)

Chromaticity Measurements:

Beam Angle: 140°

CRI: ≥ 70

R9: -21

DUV: 0.0059

Chromaticity (x,y): x=.3454; y= .3639

Chromaticity (u,v): u=.2069; v= .3270

Component Specifications:

LED: 144PCS 2835

Driver: 120-277V 50-60HZ

Driver Output Volts: 120-277

Driver Output Amps: 205mA

Surge Protection: 10,000V

Dimming: 0-10

Operating Temperature:

Minimum Starting -31° - 122° F

Construction:

Housing: Aluminum Housing

Power Coat Bronze Finish

IP Rating: Wet Location Rated

Lens Material: Prismatic Polycarbonate Lens

Mounting: Ceiling Mount

(Drywall / Sheetrock)

Listings: ETL and DLC

Carton Qty: 1

Weight: 8 lb

Warranty:

USA LEDS carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal and proper usage).